



| TECHNICAL DATA | |
|-----------------------------|-----------------|
| temperature max | 90°C |
| pressure max | 500 bar |
| flow | 60-180 l/min |
| washing cycle time | 4.8 min |
| min. pass-through hole dia. | 140 mm (manual) |
| water inlet | 1/2" G |
| inlet filter | 700 micron |
| material | INOX |
| seals | NBR |
| nozzle size | 1/4" NPT |
| nozzles positions | 2 - 4 |
| weight | 9.5 Kg |

| APERTURA DIFFUSORE DIFFUSER OPENING | | | |
|--|-----|-------|----------|
| 3 | 3/6 | 3/6/9 | 3/6/9/12 |
| 60 | 16 | 12 | 9 |
| 70 | | 15 | 11 |
| 80 | | 18 | 13 |
| 90 | | 16 | 13 |
| 100 | | 18 | 14 |
| 110 | | 18 | 14 |
| 120 | | | 16 |
| 140 | | | 18 |
| 160 | | | 20 |
| 180 | | | 22 |

PORTATA
FLOW
L/MIN

| | | | | | | |
|----------------------|---|---|---|---|---|---|
| RUGOSITA' (UNI 4600) | MODIFICA | 1 | 2 | 3 | 4 | 5 |
| FOGLIO | XXXX | | | | | |
| DATA | XX.XX.XX | | | | | |
| GREZZO | TOLLERANZE GENERALI classe m UNI-EN 22768/1 | | | | | |
| ~ = ∅ | 0±6 6±30 30±120 120±400 400±1000 1000±2000 | | | | | |
| SGROSS. | ±0.1 ±0.2 ±0.3 ±0.5 ±0.8 ±1.2 | | | | | |
| ∇ = 3/2 | NOTE: | | | | | |
| FINITURA | MATERIALE: | | | | | |
| ∇∇ = 1.6/ | | | | | | |
| ∇∇∇ = 0.8/ | DESCRIZIONE: MW 520AA 02 | | | | | |
| ∇∇∇∇ = ∇ | INSTALLATION DRAWING | | | | | |
| | DESCRIZIONE: MW 520AA 02 | | | | | |
| | INSTALLATION DRAWING | | | | | |
| | DESCRIZIONE: MW 520AA | | | | | |
| | INSTALLATION DRAWING | | | | | |

Bonomi
CLEANING HEADS

MONTECCHIO E. (RE) - ITALY

DISEGN.: CR CONTR.: DM

DATA: 29.06.11 MOD.:

SCALA

1:1 A4 O

CODICE: MW 520AA

INSTALLATION DRAWING