

ST-1500C professional spray gun



The choice of perfection



ideal for
pre-spray and pre-wash
applications in
vehicle washing

Stainless steel version



ST-1500C the professional spray gun suitable for pre-spray and pre-wash applications in vehicle washing

- stainless steel in- and outlet
- equipped with ceramic ball, chemical resistant valve
- alkali resistant PEEK sealing seat
- high quality FKM seals.
- by using PEEK as sealing seat material, the gun is also particularly suitable for pre-spray and pre-wash applications in vehicle washing
- max. 275 bar / 45 l/min / 150°C



Inner Values: High quality materials for best chemical resistance. R + M Nr. 202 000 054 can also be used for ST-2000 and ST-601.





Stainless steel:
In- and outlet.

Technical data

| Model: | ST-1500C |
|------------------------|-----------------------|
| Max. pressure | 275 bar / 4.000 psi |
| Max. flow | 45 l/min |
| Max. temperature | 150 °C |
| Inlet | rear |
| Swivel at inlet | optional |
| Chemical resistance | standard |
| Freeze stop version | optional |
| Weep version | optional |
| LTF technology | - |
| Material valve housing | brass |
| Material valve | Peek/ stainless steel |
| Food safe | - |
| One-piece valve kit | - |
| Quick coupling outlet | - |
| Progressive closing | - |
| Private label | - |

ST-1500C

TIP: With the new valve 202 000 054 our spray guns ST-2000 and ST-601 can be upgraded chemically resistant.

Professional spray gun. Ceramic ball, chemical resistant valve and acid and alkali resistant PEEK sealing seat. FKM seals. Stainless steel in- and outlet.

By using PEEK as sealing seat material, the gun is also particularly suitable for pre-spray and pre-wash applications in vehicle washing. Max. 275 bar / 45 l/min / 150 °C

| | | |
|-------------|--------|--------|
| R+M Nr. | ☺ | ☺ |
| 201 500 572 | 1/4" F | 3/8" F |